

High Temperature Filters

MODEL

F 1550 HDT

Filter capacity	l/min	155000	Flow rates at 7 bar and 20°C
	m³/h	9300	
Working pressure	bar	7 (16 max)	QF - Dust Filtration
Air connections	IN/OUT	DN 150	PF - General purpose Protection Filtration
Net weight	Kg	192	HF - High Efficiency Oil Removal Filtration
Standard type of drain	Ball valve		

Filtration grade		QF	PF	HF
Complete filter code		04G.1200.QG00	04G.1200.PG00	04G.1200.HG00
Filter element code		04E.1200GQ	04E.1200GP	04E.1200GH
Physical filtration process		Interception	Interception + coalescing	Interception + coalescing
Max solid dimension intercepted (ISO 8573-1)	µm	1 µ	0,1 µ	0,01 µ
Max solid dimension intercepted (ISO 8573-1)	Class	3	2	1
Remaining oil content after filtration (ISO 8573-1)	mg/m³	//	0,1 mg/m³	0,01 mg/m³
Remaining oil content after filtration (ISO 8573-1)	Class	//	2	1
Max temperature	°C	150	150	150
Pressure drop with new element	bar	0,05	0,1	0,1
Pressure drop with saturated elements	bar	0,4	0,4	0,4
Element replacement time	hours	4000 h	4000 h	4000 h
Element replacement time	months	6	6	6

Line pressure [bar]	1	2	3	5	7	9	11	13	15	16
Correction factor	0,38	0,53	0,65	0,85	1,00	1,13	1,25	1,36	1,46	1,51

