



# TECHNICAL DATA SHEET

Rev.02 - 22/01/2024

## High Temperature Filters

### MODEL

### F 3300 HDT

|                        |               |                 |   |
|------------------------|---------------|-----------------|---|
| Filter capacity        | l/min<br>m³/h | 331667<br>19900 | Flow rates at 7 bar and 20°C                |
| Working pressure       | bar           | 7 (16 max)      | QF - Dust Filtration                        |
| Air connections        | IN/OUT        | DN 250          | PF - General purpose Protection Filtration  |
| Net weight             | Kg            | 460             | HF - High Efficiency Oil Removal Filtration |
| Standard type of drain | Ball valve    |                 |   |

| Filtration grade                                    | QF            | PF                        | HF                        |
|---|---------------|---------------------------|---------------------------|
| Complete filter code                                | 04G.A199.QG00 | 04G.A199.PG00             | 04G.A199.HG00             |
| Filter element code                                 | 04E.A199GQ    | 04E.A199GP                | 04E.A199GH                |
| Physical filtration process                         | Interception  | Interception + coalescing | Interception + coalescing |
| Max solid dimension intercepted (ISO 8573-1)        | µm            | 1 µ                       | 0,1 µ                     |
| Max solid dimension intercepted (ISO 8573-1)        | Class         | 3                         | 2                         |
| Remaining oil content after filtration (ISO 8573-1) | mg/m³         | //                        | 0,1 mg/m³                 |
| Remaining oil content after filtration (ISO 8573-1) | Class         | //                        | 1                         |
| Max temperature                                     | °C            | 150                       | 150                       |
| Pressure drop with new element                      | bar           | 0,05                      | 0,1                       |
| Pressure drop with saturated elements               | bar           | 0,4                       | 0,4                       |
| Element replacement time                            | hours         | 4000 h                    | 4000 h                    |
| Element replacement time                            | months        | 6                         | 6                         |

|                     |      |      |      |      |      |      |      |      |      |      |
|---------------------|------|------|------|------|------|------|------|------|------|------|
| Line pressure [bar] | 1    | 2    | 3    | 5    | 7    | 9    | 11   | 13   | 15   | 16   |
| Correction factor   | 0,38 | 0,53 | 0,65 | 0,85 | 1,00 | 1,13 | 1,25 | 1,36 | 1,46 | 1,51 |

| Dimensions (mm) |      |
|-----------------|------|
| A               | 1520 |
| B               | 1050 |
| C               | 435  |
| D               | 780  |

